

Supplementary material for “Quantifying acoustic damping using flame chemiluminescence”

E. Boujo^{1†}, A. Denisov², B. Schuermans³ and N. Noiray¹

¹CAPS Lab., Mechanical and Process Engineering Dept., ETHZ, 8092 Zürich, Switzerland

²Combustion Research Lab., Paul Scherrer Institute, 5232 Villigen, Switzerland

³GE Power, 5401 Baden, Switzerland

(Received xx; revised xx; accepted xx)

† Email address for correspondence: eboujo@ethz.ch




FIGURE 1. Simultaneous fit of the gain and phase of the acoustic transfer function $H(f)$, and corresponding poles (\times) and zeros (\bullet) for different orders N and frequency ranges $f_p \pm \Delta f$: (a) $N = 2, 4$ and 6 , $\Delta f = 30$ Hz; (b) $N = 6$, $\Delta f = 20$ and 40 Hz. Bold crosses indicate the dominant pole λ_a in the vicinity of the peak frequency f_p . Equivalence ratio $\Phi = 0.538$.




FIGURE 2. Real part of the poles identified in the vicinity of the peak frequency f_p , vs. order N of the fitting transfer function. (a) $\Phi = 0.526$, (b) $\Phi = 0.538$, (c) $\Phi = 0.549$. Dashed lines show the real part σ of the identified dominant pole.